# 

BERGOLIN		BERGOLIN Greating Your Coatings
Technical data sheet		3262
		001/01.2024
Bergolin 2K-PUR-Haftvermittler 3D203, color (Series 3D203)	Page	1 of 3

### 1. Product description

**Bergolin 2K-PUR-Haftvermittler 3D203, color (Series 3D203)** is a solvent based, fast drying 2 component adhesion primer with very good adhesion on aluminum and PVC.

## 2. General information

			· · · · · · · · · · · · · · · · · · ·
Manufacturer	Bergolin GmbH & Co. KG	Contact	Tel. +49 4795 / 95899-0
	Sachsenring 1 27711 Osterholz-Scharmbeck		Fax: +49 4795 / 95899-290 E-Mail: info@bergolin.de
			Web: www.bergolin.de
Product	Bergolin 2K-PUR-Haftvermittler 3D203, color	Series	3D203
Approvals and specifications	N/A		

## 3. Product features

Binder system	PVC epoxide combination
Hardener	Bergolin Härter 7D203
Thinner	N/A
Cleaning thinner	Superdur-Verdünnung 5D402
Characteristic	Solvent based fast drying Very good adhesion
Color	Yellow glaze Other colors on request
Gloss	Glossy
Shelf life	Component A 12 months / component B 12 months In the closed original container at temperatures from +10°C to +35°C.

Modified by: Heide, Alexander	Released by: Heide, Alexander
Date: 24.01.2024	Date: 24.01.2024

# $O\!E \bullet * ^ a | ` \& o\! A \} c ^ | a ^ * o ^ a a e A \ddot{O} [ ` ` { ^ } o ^ A a & @ A a ^ ! ` } * \bullet a a ^ ! ` ] * \bullet a ^ ! ` ] * \bullet a a ^ ! ] * \bullet a ^ ! ` ] * \bullet a ^ ! ` ] * \bullet a ^ ! ` ] * \bullet a ^ ! ] * \bullet a ^ ! ] *$

BERGOLIN		BERGOLIN Creating Your Coatings
- · · · · · ·	ID	3262
Technical data sheet	Stand	001/01.2024
Bergolin 2K-PUR-Haftvermittler 3D203, color (Series 3D203)	Page	2 of 3

	A Component	B Component	Mixture
Density DIN EN ISO 2811-1/+20°C	Approx. 0.93 g/cm <sup>3</sup>	Approx. 1.13 g/cm <sup>3</sup>	Approx. 0.95 g/cm <sup>3</sup>
VOC content IE Directive 2010/75 / EU	Approx. 714 g/l	Approx. 0 g/l	Approx. 628 g/l
Solid body weight percentage: acc. MSDS	Approx. 26 %	Approx.100 %	Approx. 37 %
Viscosity +20°C	Approx. 17 Sek. / 4mm DIN 53211	Approx. 1,000 mPas DIN EN ISO 2555	Approx. 23 Sek. / 4mm DIN 53211

### 4. Processing

The following information can vary depending on the application. Please get in touch with your direct contact person for more detailed information.

Substrate	Aluminum, PVC		
Substrate pretreatment	Mechanically sand the surface; the surface must be dry and clean before application.		
Mixing ratio	6:1 by weight 7,3:1 by volume		
Mixing	Completely add the hardener component to the base component and stir intensively. Adding additional thinner is not necessary.		
Theoretical consumption	Approx. 35 g/m <sup>2</sup> per 10µm dry film thickness		
Application type	brushing Rolling		
Processing conditions	> +10°C / 20-80 % rel. humidity The dewpoint must be 3°C below the object temperature.		
Pot life +20°C	Approx. 30 min.		
Drying time *1 +20°C; 65% RH	Dust dry: approx. 10 min. Coatable: between 15 Min. and 6h		

<sup>\*1</sup> Lower temperatures slow drying. Higher temperatures accelerate drying.

Modified by: Heide, Alexander	Released by: Heide, Alexander
Date: 24.01.2024	Date: 24.01.2024

### 

BERGOLIN		BERGOLIN Creating Your Coatings
Technical data sheet		3262
		001/01.2024
Bergolin 2K-PUR-Haftvermittler 3D203, color (Series 3D203)	Page	3 of 3

# 5. Note

With this product data sheet, all previously published product data sheets lose their validity. Based on our experience, our product data sheets provide information to the best of our knowledge and serve the user's technical support. The information contained herein is based on experience under standard conditions and assuming proper storage and processing of the product. Substrates, materials, and working conditions may differ. Therefore, neither a guarantee of the results of work nor liability can be justified on whatever legal grounds on the basis of the information contained in this document or on the basis of a verbal consultation. Our technical product leaflets cannot and should not represent any guarantee of characteristics in the legal sense. Furthermore, our product data sheets do not constitute a contractual legal relationship and do not represent the contractually agreed quality of our products. A guarantee of certain properties/quality characteristics or the suitability of the product for a specific application cannot be derived from our information. The information contained herein is not binding and we assume no liability for its completeness, correctness or accuracy. This exclusion of liability does not apply to claims under the Product Liability Act, claims due to malicious, intentional or grossly negligent behavior of the contractual partners, claims arising from liability for guaranteed characteristics of the quality as well as damages from injury to life, body or health. Our general terms and conditions for sales and delivery also apply.

Our products are made exclusively for the professional industrial user who has appropriate expertise in handling and using chemical/technical surface finish products. In individual cases, the application and processing of our products requires individual coordination of the coating structure or the working process due the differing surfaces and occurring stresses. The purchaser is responsible for the examination of the product for the intended application. Preliminary tests are recommended. When applying our products, the relevant statutory regulations (in particular regulations governing hazardous substances), leaflets issued by the German Trade Association for Raw Materials and Chemical Industry (BG RCI) and the accident prevention regulations of the relevant professional association must be observed. Further details can be found in the respective safety data sheets. Processing should only be carried out under consideration of current safety regulations in the relevant country/state. We reserve the right to adapt the content of our product data sheets without prior notice to the state of the art and to supplement, update or change without prior notice and without obligation.

Modified by: Heide, Alexander	Released by: Heide, Alexander
Date: 24.01.2024	Date: 24.01.2024