

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SAFETY DATA SHEET

### FOR PROFESSIONAL and/or INDUSTRIAL USE ONLY

### **EPIKOTE<sup>™</sup> Resin MGS LR 285**

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1** Product identifier

Product name SDS Number	:	EPIKOTE <sup>™</sup> Resin MGS LR 285 16S-00006
Product type	:	Epoxy Resin
Other means of identification	:	UFI: RYCF-JSKH-2FC4-C1J2

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** 

Binder

**Identified uses** Not applicable.

Uses advised against Not applicable.

### **1.3** Details of the supplier of the safety data sheet

:	Westlake Epoxy B.V.
	Seattleweg 17
	3195 ND Pernis - Rotterdam
	The Netherlands
:	epoxyservice@westlake.com General information +31 (0) 10 295 4011
:	CARECHEM24 +44 (0) 1235 239 670
	:

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] as amended by GB-CLP</u> <u>Regulation,UK REACH Regulation SI 2019/720, and UK REACH Regulation SI 2019/1567</u>

Acute Tox. 4 H302 Skin Corr./Irrit. 2 H315 Eye Dam./Irrit. 2 H319 Skin Sens. 1 H317 Aquatic Chronic 2 H411

See Section 16 for the full text of the H statements declared above.

#### 2.2 Label elements

Hazard pictograms Signal word

Hazard statements

Warning
Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

Prevention	<ul> <li>Wear protective gloves.</li> <li>Wear eye or face protection.</li> <li>Avoid release to the environment.</li> <li>Avoid breathing vapor.</li> <li>Do not eat, drink or smoke when using this product.</li> <li>Wash thoroughly after handling.</li> </ul>
Response	<ul> <li>Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.</li> </ul>
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,2,3-Propanetriol, polymer with 2-(chloromethyl)oxirane
Version: 5.1	Date of issue/Date of revision:08.08.2024Date of previous issue:04.01.2023

EPIKOTE<sup>™</sup> Resin MGS LR 285

Page:3/17

Supplemental label elements	:	Not applicable. Not applicable.

### 2.3 Other hazards

Product meets the criteria for	:	This mixture does not contain any substances that are assessed to be
PBT or vPvB according to		a PBT or a vPvB.
<b>Regulation (EC) No. 1907/2006,</b>		
Annex XIII		
Other hazards which do not	:	None known.
result in classification		

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	:	Mixture			
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M- factors and ATEs	Туре
bis-[4-(2,3- epoxipropoxi)phenyl]pro pane	RRN : UK-01- 4433604119-7 EC : 216-823-5 CAS : 1675-54-3 Index : 603-073-00-2		Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2,3-Propanetriol, polymer with 2- (chloromethyl)oxirane	CAS : 25038-04-4	>= 50 - <= 75	Acute Tox. 4, H302 Skin Irrit. 2, H315	-	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### **4.1** Description of first aid measures

Eye contact	upper and	l lower eyelids.	ith plenty of water, occasion Check for and remove any ast 10 minutes. Get medica	contact lenses.
Inhalation	: Remove for breath	victim to fresh a ning. If not breat	ir and keep at rest in a posi hing, if breathing is irregul provide artificial respiratio	tion comfortable lar or if
	trained pe give mou	ersonnel. It may th-to-mouth resu	be dangerous to the persor uscitation. Get medical atte re severe. If unconscious, p	n providing aid to ention if adverse
Version: 5.1	Date of issue/Date of revision:	1	Date of previous issue:	04.01.2023

Page:4/17

Skin contact	:	position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first aid personnel	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### **4.2** Most important symptoms and effects, both acute and delayed

### Potential acute health effects

Eye contact Inhalation Skin contact Ingestion Over-exposure signs/symptoms	:	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. Harmful if swallowed.
<u> </u>		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Inhalation Skin contact	:	pain or irritation watering redness No specific data. Adverse symptoms may include the following: irritation redness

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	:	Treat symptomatically. Contact poison treatment specialist
		immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.

### **SECTION 5: Firefighting measures**

Version: 5.1

EPIKOTE<sup>™</sup> Resin MGS LR 285

Page:5/17

### **5.1** Extinguishing media

Suitable extinguishing media	:	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	:	Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
<b>5.3</b> Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Additional information	:	Not available

### **SECTION 6: Accidental release measures**

### **6.1** Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for contai	nme	nt and cleaning up
Small spill Large spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water- insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Approach
		release from upwind. Prevent entry into sewers, water courses,

 Version:
 5.1
 Date of issue/Date of revision:
 08.08.2024
 Date of previous issue:
 04.01.2023

EPIKOTE<sup>™</sup> Resin MGS LR 285

		basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

Recommendations	:	Not available
Industrial sector specific	:	Not available
solutions		

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Occupational exposur No exposure limit valu				
Recommended monit		oduct contains	ingredients with exposure l	imits, personal,
Version: 5.1	Date of issue/Date of revision:	08.08.2024	Date of previous issue:	04.01.2023

### procedures

workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredie	Туре	Exposure	Value	Population	Effects
nt name					
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Dermal	8.3 mg/kg bw/day	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Inhalation	12.3 mg/m <sup>3</sup>	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Dermal	8.3 mg/kg bw/day	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Inhalation	12.3 mg/m <sup>3</sup>	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Dermal	3.6 mg/kg bw/day	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Inhalation	0.75 mg/m <sup>3</sup>	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Dermal	3.6 mg/kg bw/day	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Inhalation	0.75 mg/m <sup>3</sup>	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Oral	0.75 mg/kg bw/day	General population	Systemic
DNEL/DMEL Su	mmary	: Not ava	ailable		

### **PNECs**

Product/ingredient name	Туре	<b>Compartment Detail</b>	Value	Method Detail
bis-[4-(2,3-	PNEC	Fresh water	6 µg/l	
epoxipropoxi)phenyl]prop				
ane				
bis-[4-(2,3-	PNEC	Marine	1 μg/l	
epoxipropoxi)phenyl]prop				
ane				
bis-[4-(2,3-	PNEC	Sewage Treatment Plant	10 mg/l	
epoxipropoxi)phenyl]prop				
ane				
bis-[4-(2,3-	PNEC	Fresh water sediment	0.341 mg/kg dw	
epoxipropoxi)phenyl]prop				

ane				
bis-[4-(2,3-	PNEC	Marine water sediment	0.034 mg/kg dw	
epoxipropoxi)phenyl]prop				
ane				
bis-[4-(2,3-	PNEC	Soil	0.065 mg/kg dw	
epoxipropoxi)phenyl]prop				
ane				

**PNEC Summary** 

Not available

### Derived No-Effect Levels' (DNEL's) and Predicted No-Effect Concentrations' (PNEC's)

:

#### **Explanatory note:**

REACH requires manufacturers and importers to establish and report 'Derived No-Effect Levels' (DNEL's) for humans by inhalation, ingestion and dermal routes of exposure and 'Predicted No-Effect Concentrations' (PNEC's) for environmental exposure. DNEL's and PNEC's are established by the registrant without an official consultation process, and are not intended to be directly used for setting workplace or general population exposure limits. They are primarily used as input values in running Quantitative Risk Assessment models (like the ECETOC-TRA model).

Due to differences in calculation methodology the DNEL will tend to be lower (sometimes significantly) than any corresponding health-based OEL for that chemical substance. Further although DNEL's (and PNEC's) are an indication for setting risk reduction measures, it should be recognized that these limits do not have the same regulatory application as officially endorsed governmental OEL's.

#### 8.2 Exposure controls

Appropriate engineering controls	:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material
Version: 5.1 Date of issue	/Date	of revision:         08.08.2024         Date of previous issue:         04.01.2023

Conforms to Regulation (EC) No. 19 EPIKOTE <sup>™</sup> Resin MGS LR 285	907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Page:9/17
	may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	<ul> <li>Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use</li> </ul>

#### proper fitting, training, and other important aspects of use. **Environmental exposure controls** Emissions from ventilation or work process equipment should be : checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

### Appearance

Physical state Color	:	liquid Yellowish.
Odor	:	slight, characteristic
Odor threshold	:	Not available (not measured)
рН	:	Not available (not measured)
Melting point/freezing point	:	Not available (not measured)
Initial boiling point and boiling	:	Not available (not measured)
range		
Flash point	:	Greater than 100 °C
Evaporation rate	:	Not available (not measured)
Upper/lower flammability or	:	Lower: Not available (not measured)
explosive limits		<b>Upper:</b> Not available (not measured)
Vapor pressure	:	Not available (not measured)
Vapor density	:	Not available (not measured)
Relative density	-	Not available (not measured)
Density	:	Approx. 1.140 g/cm3
Solubility(ies)	:	Not available (not measured)
Solubility in water	:	Insoluble
Partition coefficient: n-	:	Not applicable.
octanol/water		
Auto-ignition temperature	:	Not available (not measured)
Decomposition temperature	:	Not available (not measured)
Viscosity	:	<b>Dynamic:</b> Approx. 600 - 900 mPa·s @ 25 °C (ISO 9371)
·		
		Kinematic: Not available (not measured)
		Kinematic: Not available (not measured)

EPIKOTE<sup>™</sup> Resin MGS LR 285

Page:10/17

Explosive properties Oxidizing properties	:	Not available (not measured) Not available (not measured)
Particle characteristics		
Median particle size	:	Not applicable.

### 9.2 Other information

No additional information.

### **SECTION 10: Stability and reactivity**

10.1 Reactivity	:	Stable under normal conditions.
<b>10.2</b> Chemical stability	:	The product is stable.
<b>10.3</b> Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4</b> Conditions to avoid	:	No specific data.
<b>10.5</b> Incompatible materials	:	No specific data.
<b>10.6 Hazardous decomposition</b> products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

**Conclusion/Summary** Not available :

### Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
	1000 mg/kg	N/A	N/A	N/A	N/A
1,2,3-Propanetriol, polymer with 2- (chloromethyl)oxirane	500 mg/kg	N/A	N/A	N/A	N/A

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-	Skin -	Rabbit	1.5 - 2		-
epoxipropoxi)phenyl]propane	Erythema/Eschar				
	404 Acute Dermal				

Page:11/17

Irritation/Corrosion				
Skin - Edema 404	Rabbit	1.0 - 1.5		-
Acute Dermal				
Irritation/Corrosion				
Eyes 405 Acute	Rabbit	0		-
Eye				
Irritation/Corrosion				
Eyes - Redness of	Rabbit	0.7		-
the conjunctivae				
Skin - Moderate	Rabbit	-	24 hrs	-
irritant				
Skin - Severe	Rabbit	-	24 hrs	-
irritant				
Eyes - Mild irritant	Rabbit	-		-

### Conclusion/Summary

Skin	: Not ava	ailable
Eyes	: Not ava	ailable
Respiratory	: Not ava	ailable

### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result			
bis-[4-(2,3-	Skin	See Remarks	Sensitizing			
epoxipropoxi)phenyl]propan						
e						
Remarks:	concentration of 5.7% sug this test system. In an OE induced positive dermal r concentration challenge d sensitizer under the condi	In an OECD No. 429 mouse LLNA study the estimated EC3 was a concentration of 5.7% suggesting that BADGE is a moderate skin sensitizer in this test system. In an OECD No. 406 guinea pig Maximization study BADGE induced positive dermal reaction in 100% of the test animals at a 50% concentration challenge dose. Therefore, BADGE is an "Extreme" skin sensitizer under the conditions of this study. BADGE was also positive for skin sensitization in an OECD No. 406 guinea pig Buehler method study.				
<b>Conclusion/Summary</b>						
Skin	: Not available	e				
Respiratory	: Not available	e				

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result			
bis-[4-(2,3-	-	Subject: Mammalian-	Negative			
epoxipropoxi)phenyl]prop		Animal				
ane						
Remarks:	oral gavage study conducte mouse micronucleus test co in a male mouse spermatoc oral gavage up to a high do frequency of chromosome of cytogenetic test by oral gav	Did not induce evidence of chromosome damage in a mouse dominant lethal oral gavage study conducted up to a high dose level of 10 grams/kg and in a mouse micronucleus test conducted up to a high dose of 5000 mg/kg. Negati- in a male mouse spermatocyte cytogenetic assay with treatment for 5 days by oral gavage up to a high dose of 3000 mg/kg. Did not induce an increase in th frequency of chromosome damage in a Chinese hamster bone marrow cytogenetic test by oral gavage up to a high dose of 3300 mg/kg. Failed to induce an increase of DNA strand breaks in rat liver cells following oral gava				
<b>Conclusion/Summary</b>	: Not available					

### **Carcinogenicity**

<b>Conclusion/Summary</b>	: Not avai	lable		
Version: 5.1	Date of issue/Date of revision:	08.08.2024	Date of previous issue:	04.01.2023

EPIKOTE<sup>™</sup> Resin MGS LR 285

Page:12/17

<u>Reproductive toxicity</u>		
Conclusion/Summary	:	Not available
<b>Teratogenicity</b>		
Conclusion/Summary	:	Not available
Specific target organ toxicity (sing Not available	<u>le ex</u>	posure)
Specific target organ toxicity (rependent) Not available	eated	exposure)
Aspiration hazard Not available		
Information on likely routes of exposure	:	Not available
Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	::	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. Harmful if swallowed.
Symptoms related to the physical, c	hemi	ical and toxicological characteristics
Eye contact Inhalation Skin contact	: : :	Adverse symptoms may include the following: pain or irritation, watering, redness No specific data. Adverse symptoms may include the following: irritation, redness
Ingestion	:	No specific data. chronic effects from short and long-term exposure
Short term exposure	<u>II as</u>	
Potential immediate effects Potential delayed effects	:	Not available Not available
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available Not available
Potential chronic health effects		
Conclusion/Summary	:	Not available
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity Mutagenicity	:	No known significant effects or critical hazards.
Mutagenicity Reproductive toxicity	:	No known significant effects or critical hazards. No known significant effects or critical hazards.
	e/Dat	e of revision: 08.08.2024 Date of previous issue: 04.01.2023

EPIKOTE<sup>™</sup> Resin MGS LR 285

Page:13/17

### 11.2. Information on other hazards

<b>11.2.1</b> Endocrine disrupting properties	:	Not av
11.2.2 Other information	:	Not av

- **11.2.2** Other information
- vailable Not available

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure			
bis-[4-(2,3-epoxipropoxi)phen	bis-[4-(2,3-epoxipropoxi)phenyl]propane					
	Acute LC50 1.3 mg/l - 203	Fish	96 h			
	Fish, Acute Toxicity Test					
	Acute EC50 2.1 mg/l - 202	Water flea	48 h			
	Daphnia sp. Acute					
	Immobilization Test and					
	Reproduction Test					
	Acute LC50 > 11 mg/l -	Algae	72 h			
	Chronic NOEC 0.3 mg/l semi-	Water flea	21 d			
	static test 211 Daphnia Magna					
	Reproduction Test					

**Conclusion/Summary** 

Not available

:

:

### 12.2 Persistence and degradability

**Conclusion/Summary** 

Not available

### **12.3** Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential	
bis-[4-(2,3-	2.64 - 3.78	3 - 31 31.00	low	
epoxipropoxi)phenyl]propane				

### 12.4 Mobility in soil

Soil/water partition coefficient	:	Not available
(KOC)		
Mobility	:	Not available

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

<b>12.6</b> Endocrine disrupting properties	:	Not available
<b>12.7</b> Other adverse effects	:	No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Version: 5.1

EPIKOTE<sup>™</sup> Resin MGS LR 285

Version: 5.1

04.01.2023

Date of previous issue:

### **Product**

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the
Hazardous waste	<ul><li>requirements of all authorities with jurisdiction.</li><li>The classification of the product may meet the criteria for a hazardous waste.</li></ul>
<b>Packaging</b>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

<b>Regulatory</b> information	14.1. UN number	14.2. UN proper shipping name	14.3. Transpor hazard class(e		
ADR/ADN	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III	
RID	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III	
ICAO/IATA	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III	
IMO/IMDG	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III	
14.5. Environmental hazards					
Environmentall	ly hazardous	and/or Marine Pollutant	: Yes.	La V	

Date of issue/Date of revision: 08.08.2024

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 EPIKOTE<sup>™</sup> Resin MGS LR 285 Page:15/17 14.6 Special precautions for user Transport within user's premises: always transport in closed : containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. 14.7 Maritime transport in bulk Not available : according to IMO instruments

### **SECTION 15:** Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization Annex XIV None required.

Substances of very high concern None required.

Annex XVII - Restrictions on : the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Prior Informed Consent (PIC) (649/2012/EU) None required.

**Seveso Directive** This product is controlled under the Seveso Directive.

#### **Danger criteria**

Category	
E2	

#### **International regulations**

Version: 5.1

International lists	: Australia inventory (AICS). All components are listed or exempted.
	Canada inventory. All components are listed or exempted.
	Japan inventory Not determined.
	China inventory (IECSC). All components are listed or exempted.
	Korea inventory (KECI) All components are listed or exempted.
	New Zealand Inventory (NZIoC) Not determined.
	Philippines inventory (PICCS). Not determined.
	United States inventory (TSCA 8b). All components are active or exempted.
	Taiwan inventory (TCSI). All components are listed or exempted.
	Thailand inventory Not determined.
	Vietnam inventory Not determined.

08.08.2024

Date of previous issue: 04.01.2023

Date of issue/Date of revision:

**15.2** Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

Abbreviations and acronyms	:	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
		$v_1 v_2 = v_1 v_1 v_1 v_1 v_1 v_1 v_1 v_1 v_1 v_1$

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

### Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

Skin Irrit. 2	SKIN CORROSION/IRRITATION
Skin Sens. 1	SKIN SENSITIZATION
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM)
Skin Irrit. 2	SKIN CORROSION/IRRITATION
Skin Sens. 1	SKIN SENSITIZATION
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM)
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1

03.10.2024

Date of issue/ Date of revision Version: 5.1 Date : 08.08.2024

Date of issue/Date of revision: 08.08.2024

:

Date of previous issue: 04.01.2023

EPIKOTE<sup>™</sup> Resin MGS LR 285

Page:17/17

Date of previous issue	:	04.01.2023
Version	:	5.1

### Notice to reader

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.