

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

# SAFETY DATA SHEET

# FOR PROFESSIONAL and/or INDUSTRIAL USE ONLY

### EPIKOTE™ Resin MGS RIMR 035c

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### 1.1 Product identifier

**Product name** : EPIKOTE<sup>TM</sup> Resin MGS RIMR 035c

SDS Number : BAK0000399

**Product type** : Resin

Other means of identification : UFI: PP2S-10NU-100Y-T7AT

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use Binder

**Identified uses** Not applicable.

Uses advised against

Not applicable.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier/Importer : Westlake Epoxy B.V.

Seattleweg 17

3195 ND Pernis - Rotterdam

The Netherlands

**Contact person** : epoxyservice@westlake.com

**Telephone** : General information

+31 (0) 10 295 4011

1.4

**Emergency telephone number** 

 Supplier
 : CARECHEM24

 Telephone number
 : +44 (0) 1235 239 670

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] as amended by GB-CLP Regulation, UK REACH Regulation SI 2019/720, and UK REACH Regulation SI 2019/1567

Skin Corr./Irrit. 2 H315 Eye Dam./Irrit. 2 H319 Skin Sens. 1 H317 Repr. 1B H360F Aquatic Chronic 2 H411

See Section 16 for the full text of the H statements declared above.

### 2.2 Label elements

. TT 1 . .

Hazard pictograms

**\$** 



Signal word : Danger

**Hazard statements** : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility.

Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

**Prevention**: Obtain special instructions before use.

Wear protective gloves, protective clothing, eye protection, face

protection, or hearing protection. Avoid release to the environment. Avoid breathing vapor.

Wash thoroughly after handling.

**Response** : Collect spillage.

IF exposed or concerned: Get medical advice or attention.

Take off contaminated clothing and wash it before reuse.

IF ON SKIN:

Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If eye irritation persists:

Get medical advice or attention.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Hazardous ingredients** : bis-[4-(2,3-epoxipropoxi)phenyl]propane

Bisphenol F diglycidyl ether, reaction mass of isomers oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

**Supplemental label elements** 

Not applicable. Not applicable.

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Annex XIII
Other hazards which do not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

None known.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M- factors and ATEs	Туре
bis-[4-(2,3- epoxipropoxi)phenyl]pro pane	RRN: 01- 2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	>= 50 - <= 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Bisphenol F diglycidyl ether, reaction mass of isomers	RRN: 01- 2119454392-40 EC: 701-263-0	>= 10 - <= 25	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
	RRN: 01- 2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4		Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360F	-	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### **Type**

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

EPIKOTE™ Resin MGS RIMR 035c Page:4/20

### **4.1** Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If

unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

a collar, tie, belt or waistband.

**Skin contact**: Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. If material has

been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical

attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

a collar, tie, belt or waistband.

**Protection of first aid personnel**: No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact** : Adverse symptoms may include the following:

EPIKOTE™ Resin MGS RIMR 035c Page:5/20

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).

: Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide halogenated compounds

### **5.3** Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece

operated in positive pressure mode.

**Additional information** : Not available

# **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any pe

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate

EPIKOTE™ Resin MGS RIMR 035c

Page:6/20

### For emergency responders

ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **6.2** Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

### Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

### **6.4** Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

### **Protective measures**

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering

EPIKOTE™ Resin MGS RIMR 035c Page:7/20

eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

**Recommendations** : Not available **Industrial sector specific** : Not available

solutions

# **SECTION 8: Exposure controls/personal protection**

### **8.1** Control parameters

### **Occupational exposure limits**

No exposure limit value known. **Recommended monitoring procedures** 

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredie	Type	Exposure	Value	Population	Effects
nt name					
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Dermal	8.3 mg/kg bw/day	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Inhalation	12.3 mg/m³	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Dermal	8.3 mg/kg bw/day	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Long term Inhalation	12.3 mg/m³	Workers	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Dermal	3.6 mg/kg bw/day	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe nyl]propane	DNEL	Short term Inhalation	0.75 mg/m <sup>3</sup>	General population	Systemic
bis-[4-(2,3- epoxipropoxi)phe	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic

nyl]propane					
bis-[4-(2,3-	DNEL	Long term	3.6 mg/kg	General	Systemic
epoxipropoxi)phe		Dermal	bw/day	population	
nyl]propane					
bis-[4-(2,3-	DNEL	Long term	$0.75 \text{ mg/m}^3$	General	Systemic
epoxipropoxi)phe		Inhalation		population	
nyl]propane bis-[4-(2,3-	DNEL	Longtorm	0.75 mg/kg	General	Systemic
epoxipropoxi)phe	DNEL	Long term Oral	bw/day	population	Systemic
nyl]propane		Orai	o w/day	population	
Bisphenol F	DNEL	Short term	8.3 μg/cm <sup>2</sup>	Workers	Local
diglycidyl ether,	21,22	Dermal	0.0 µg/0	1, 0111015	2004
reaction mass of					
isomers					
Bisphenol F	DNEL	Long term	104.15 mg/kg	Workers	Systemic
diglycidyl ether,		Dermal	bw/day		
reaction mass of					
isomers					
Bisphenol F	DNEL	Long term	29.39 mg/m <sup>3</sup>	Workers	Systemic
diglycidyl ether,		Inhalation			
reaction mass of					
isomers					
Bisphenol F	DNEL	Long term	62.5 mg/kg	General	Systemic
diglycidyl ether,		Dermal	bw/day	population	
reaction mass of					
isomers					
Bisphenol F	DNEL	Long term	8.7 mg/m <sup>3</sup>	General	Systemic
diglycidyl ether,		Inhalation		population	
reaction mass of					
isomers					
Bisphenol F	DNEL	Long term	6.25 mg/kg	General	Systemic
diglycidyl ether,		Oral	bw/day	population	
reaction mass of					
isomers					
DMET /DMET C		NI-4:	1 - 1 - 1 -	•	

**DNEL/DMEL Summary** 

: Not available

### **PNECs**

Product/ingredient name	Type	<b>Compartment Detail</b>	Value	Method Detail
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	PNEC	Fresh water	6 μg/l	
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	PNEC	Marine	1 μg/l	
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	PNEC	Sewage Treatment Plant	10 mg/l	
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	PNEC	Fresh water sediment	0.341 mg/kg dw	
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	PNEC	Marine water sediment	0.034 mg/kg dw	

EPIKOTE™ Resin MGS RIMR 035c Page:9/20

bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	PNEC	Soil	0.065 mg/kg dw
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	PNEC	Soil	61.42 mg/kg dw

PNEC Summary : Not available

Derived No-Effect Levels' (DNEL's) and Predicted No-Effect Concentrations' (PNEC's)

### **Explanatory note:**

REACH requires manufacturers and importers to establish and report 'Derived No-Effect Levels' (DNEL's) for humans by inhalation, ingestion and dermal routes of exposure and 'Predicted No-Effect Concentrations' (PNEC's) for environmental exposure. DNEL's and PNEC's are established by the registrant without an official consultation process, and are not intended to be directly used for setting workplace or general population exposure limits. They are primarily used as input values in running Quantitative Risk Assessment models (like the ECETOC-TRA model).

Due to differences in calculation methodology the DNEL will tend to be lower (sometimes significantly) than any corresponding health-based OEL for that chemical substance. Further although DNEL's (and PNEC's) are an indication for setting risk reduction measures, it should be recognized that these limits do not have the same regulatory application as officially endorsed governmental OEL's.

### **8.2** Exposure controls

**Appropriate engineering controls** 

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

EPIKOTE™ Resin MGS RIMR 035c Page:10/20

Material: 898 Butoject

Minimum break through time: 480 min

Producer: This recommendation is valid only for our Product as delivered. If this product will be mixed with other substances you need to contact a supplier of CE approved protective gloves (e.g. KCL GmbH, D-36124 Eichenzell, Tel. 0049 (0) 6659 87300, Fax.

0049 (0) 6659 87155, email: vertrieb@kcl.de).

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.Other skin protectionAppropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks

involved and should be approved by a specialist before handling this

product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator

that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure controls**: Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

### **Appearance**

Physical state : liquid Color : Yellowish.

Odor : Characteristic.

Odor threshold:Not available (not measured)pH:Not available (not measured)Melting point/freezing point:Not available (not measured)

**Initial boiling point and boiling** : Greater than 200 °C

range

Flash point : Greater than 150 °C

**Evaporation rate** : Not available (not measured)

Upper/lower flammability or : Lower: Not available (not measured)

**explosive limits Upper:** Not available (not measured)

Vapor pressure : Less than 0.1 hPa

Vapor density: Not available (not measured)Relative density: Not available (not measured)Density: Approx. 1.13 g/cm3

**Solubility(ies)** : Not available (not measured)

**Solubility in water** : Partial

EPIKOTE™ Resin MGS RIMR 035c Page:11/20

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature Decomposition temperature** 

Not available (not measured)Not available (not measured)

Viscosity

**Dynamic:** Approx. 1,250 mPa·s @ 25 °C

**Kinematic:** Not available (not measured)

**Explosive properties** Oxidizing properties

Not available (not measured)Not available (not measured)

Particle characteristics

Median particle size : Not applicable.

#### 9.2 Other information

No additional information.

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : Stable under normal conditions.

**10.2 Chemical stability** : The product is stable.

**10.3** Possibility of hazardous reactions

Hazardous reactions or instability may occur under certain conditions of storage or use.

10.4 Conditions to avoid

: Caustic soda (sodium hydroxide) can induce vigorous polymerisation at temperatures around 200 °C.

10.5 Incompatible materials

Reactive or incompatible with the following materials: strong oxidizing agents, sodium hydroxide,
Strong Acids

**10.6** Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with caustic soda. Reacts exothermically with bases (eg caustic soda), ammonia, primary and secondary amines, alcohols, water and acids. Reacts with strong oxidising agents.

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure		
bis-[4-(2,3-epoxipropoxi)phenyl]propane						
	LD50 Oral	Rat	11,400 mg/kg	-		
	LD50 Dermal	Rat	2,000 mg/kg	-		
Bisphenol F diglycidyl ether, reaction mass of isomers						
	LD50 Oral	Rat	> 2,000 mg/kg	-		

	LD50 Dermal	Rabbit	> 2,000 mg/kg	-		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.						
	LD50 Oral	Rat	17,100 mg/kg	-		
	LD50 Oral	Rat	26,800 mg/kg	-		
	LD50 Dermal	Rabbit	> 4,000 mg/kg	-		

Conclusion/Summary : Not available

### **Acute toxicity estimates**

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
bis-[4-(2,3- epoxipropoxi)phenyl]propan e	11400 mg/kg	N/A	N/A	N/A	N/A
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	17100 mg/kg	N/A	N/A	N/A	N/A

# Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-	Skin -	Rabbit	1.5 - 2		-
epoxipropoxi)phenyl]propane	Erythema/Eschar				
	404 Acute Dermal				
	Irritation/Corrosion				
	Skin - Edema 404	Rabbit	1.0 - 1.5		-
	Acute Dermal				
	Irritation/Corrosion				
	Eyes 405 Acute	Rabbit	0		-
	Eye				
	Irritation/Corrosion				
	Eyes - Redness of	Rabbit	0.7		-
	the conjunctivae				
	Skin - Moderate	Rabbit	-	24 hrs	-
	irritant				
	Skin - Severe	Rabbit	-	24 hrs	-
	irritant				
	Eyes - Mild irritant	Rabbit	-		-
Bisphenol F diglycidyl ether,	Skin -	Rabbit	0.7	4 hrs	72 hrs
reaction mass of isomers	Erythema/Eschar				
	404 Acute Dermal				
	Irritation/Corrosion				
	Skin - Edema 404	Rabbit	0	4 hrs	4 - 504 hrs
	Acute Dermal				
	Irritation/Corrosion				
	Eyes - Cornea	Rabbit	0		1 - 168 hrs
	opacity 405 Acute				
	Eye				
	Irritation/Corrosion				
	Eyes - Iris lesion	Rabbit	0		1 - 168 hrs
	405 Acute Eye				
	Irritation/Corrosion				
	Eyes - Redness of	Rabbit	0		1 - 168 hrs

	the conjunctivae 405 Acute Eye Irritation/Corrosion Eyes - Edema of the conjunctivae	Rabbit	0		1 - 168 hrs
	405 Acute Eye Irritation/Corrosion				
	Skin - Mild irritant	Rabbit	-	24 hrs	-
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Skin - Primary dermal irritation index (PDII) OTS 798.4470 Acute Dermal Irritation	Rabbit	4.1	24 hrs	72 hrs
	Skin - Primary dermal irritation index (PDII) 404 Acute Dermal Irritation/Corrosion	Rabbit	5.75	24 hrs	72 hrs
	Eyes - Cornea opacity 405 Acute Eye Irritation/Corrosion	Rabbit	2		1 - 24 hrs
	Skin - Moderate irritant	Rabbit	-	24 hrs	-

Conclusion/Summary

Skin:Not availableEyes:Not availableRespiratory:Not available

### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result		
bis-[4-(2,3-	Skin	See Remarks	Sensitizing		
epoxipropoxi)phenyl]propan					
e					
Remarks:	In an OECD No. 429 mou	se LLNA study the estimate	ed EC3 was a		
	concentration of 5.7% sug	gesting that BADGE is a mo	oderate skin sensitizer in		
	this test system. In an OE	CD No. 406 guinea pig Max	ximization study BADGE		
	induced positive dermal re	eaction in 100% of the test a	nimals at a 50%		
	concentration challenge do	ose. Therefore, BADGE is a	an "Extreme" skin		
	sensitizer under the condit	ions of this study. BADGE	was also positive for skin		
	sensitization in an OECD	No. 406 guinea pig Buehler	method study.		
oxirane, mono[(C12-14-	Skin	Guinea pig	Sensitizing		
alkyloxy)methyl] derivs.					
Remarks:		A. OTS test guideline no. 87			
	study demonstrating positive dermal reactions in 20/20 guinea pigs. An				
	extreme sensitizer in an O.E.C.D. test guideline no. 406 guinea pig				
	Maximization study.				
	Skin	Guinea pig	Sensitizing OECD Test		
			Guideline 406		

Conclusion/Summary

Skin: Not availableRespiratory: Not available

### Mutagenicity

Test	Experiment	Result				
-	Subject: Mammalian-	Negative				
	Animal					
ss: Did not induce evidence of chromosome damage in a mouse dominant lethal						
		• •				
oral gavage up to a high dose of 3000 mg/kg. Did not induce an increase in the						
, , , , , , , , , , , , , , , , , , , ,		-				
treatment with 500 mg/kg a						
-		Negative				
	**					
	Experiment: In vivo					
When Bisphenol F Diglycic	dylether was evaluated for ge	notoxicity potential in				
multiple GLP in vivo assay	s including the mouse microi	nucleus, rat in vivo/in				
vitro UDS and MutaMouse tests no evidence of genotoxicity was observed. The						
results of other in vivo tests for genotoxicity also supported these negative						
findings for BPFDGE. Therefore, Bisphenol F Diglycidylether is not genotoxic						
in vivo.						
	Did not induce evidence of oral gavage study conducte mouse micronucleus test coin a male mouse spermatoc oral gavage up to a high do frequency of chromosome ocytogenetic test by oral gavinduce an increase of DNA treatment with 500 mg/kg at the state of the state o	Did not induce evidence of chromosome damage in a moral gavage study conducted up to a high dose level of 1 mouse micronucleus test conducted up to a high dose of in a male mouse spermatocyte cytogenetic assay with trooral gavage up to a high dose of 3000 mg/kg. Did not in frequency of chromosome damage in a Chinese hamster cytogenetic test by oral gavage up to a high dose of 3300 induce an increase of DNA strand breaks in rat liver cell treatment with 500 mg/kg as measured by alkaline elution.  Subject: Mammalian-Animal Experiment: In vivo  When Bisphenol F Diglycidylether was evaluated for gemultiple GLP in vivo assays including the mouse micror vitro UDS and MutaMouse tests no evidence of genotox results of other in vivo tests for genotoxicity also suppor findings for BPFDGE. Therefore, Bisphenol F Diglycidy in vivo.				

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Developmen t toxin	Species	Dose	Exposure
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	Positive	-	Rat	Oral: 10 mg/kg/d Repeated dose 443 Extended One- Generation Reproductive Toxicity Study	-

Conclusion/Summary : Not available

**Teratogenicity** 

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Not available

**Specific target organ toxicity (repeated exposure)** 

Not available

**Aspiration hazard** 

Not available

**Information on likely routes of** : Not available

exposure

EPIKOTE™ Resin MGS RIMR 035c Page:15/20

### Potential acute health effects

**Eve contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following: pain or irritation,

watering, redness

**Inhalation** : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

**Skin contact**: Adverse symptoms may include the following: irritation, redness,

reduced fetal weight, increase in fetal deaths, skeletal malformations

**Ingestion**: Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Short term exposure**

Potential immediate effects : Not available
Potential delayed effects : Not available

### Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
oxirane, mono[(C12-14-	NOAEL Dermal	Rat	1 mg/kg/d	90 days Repeated
alkyloxy)methyl] derivs.			Repeated dose	dose; 5 days per
			411 Subchronic	week Repeated
			Dermal Toxicity:	dose
			90-day Study	

Conclusion/Summary : Not available

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.

**Reproductive toxicity** : May damage fertility.

### 11.2. Information on other hazards

**11.2.1 Endocrine disrupting properties** : Not available **11.2.2 Other information** : Not available

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)phe	nyl]propane		
	Acute LC50 1.3 mg/l - 203	Fish	96 h
	Fish, Acute Toxicity Test		
	Acute LC50 1.3 mg/l 203	Fish	96 h
	Fish, Acute Toxicity Test		
	Acute EC50 2.1 mg/l - 202	Water flea	48 h
	Daphnia sp. Acute		
	Immobilization Test and		
	Reproduction Test		
	Acute LC50 $> 11 \text{ mg/l}$ -	Algae	72 h
	Acute LC50 > 11 mg/l	Algae	72 h
	Chronic NOEC 0.3 mg/l semi-	Water flea	21 d
	static test 211 Daphnia Magna		
	Reproduction Test		
Bisphenol F diglycidyl ether,	reaction mass of isomers		
	Acute LC50 2.54 mg/l	Fish	96 h
	Acute EC50 2.55 mg/l - 202	Water flea	48 h
	Daphnia sp. Acute		
	Immobilization Test and		
	Reproduction Test		
	Acute EC50 > 1,000 mg/l 201	Algae	72 h
	Alga, Growth Inhibition Test		
oxirane, mono[(C12-14-alkyl			
	Acute LC50 $> 1.8 \text{ g/l} - 203$	Rainbow trout, donaldson	96 h
	Fish, Acute Toxicity Test	trout	
	Acute LC50 $> 5.0 \text{ g/l} - 203$	Bluegill	96 h
	Fish, Acute Toxicity Test		
	Acute LC50 $> 100.0 \text{ mg/l} - 203$	Rainbow trout,donaldson	96 h
	Fish, Acute Toxicity Test	trout	
	Acute EC50 7.2 mg/l - 202	Water flea	48 h
	Daphnia sp. Acute		
	Immobilization Test and		
	Reproduction Test		
	Acute EC50 844 mg/l - 201	Algae	72 h
	Alga, Growth Inhibition Test		
	Acute EC50 844 mg/l 201	Algae	72 h
	Alga, Growth Inhibition Test		

Conclusion/Summary : Not available

### **12.2** Persistence and degradability

**Conclusion/Summary** : Not available

# 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
bis-[4-(2,3-	2.64 - 3.78	3 - 31 31.00	low
epoxipropoxi)phenyl]propane			
Bisphenol F diglycidyl ether,	3.3	150	low
reaction mass of isomers			
oxirane, mono[(C12-14-	3.77	160 - 263 160.00	low
alkyloxy)methyl] derivs.			

EPIKOTE™ Resin MGS RIMR 035c Page:17/20

### 12.4 Mobility in soil

**Soil/water partition coefficient** : Not available

(KOC)

**Mobility** : Not available

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties** : Not available

**12.7 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### **Product**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of all authorities with jurisdiction.

**Hazardous waste**: The classification of the product may meet the criteria for a

hazardous waste.

### **Packaging**

Methods of disposal : The generation of waste should be avoided or minimized wherever

possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions**: This material and its container must be disposed of in a safe way.

Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

Regulatory 14.1. UN 14.2. UN proper shipping name 14.3. Transport 14.4. Packing information number 14.3. Transport proper shipping name 14.3. Transport proper

ADR/ADN 3082 ENVIRONMENTALLY 9 III HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (EPOXIDE DERIVATIVES)

EPIKOTE™ Resin MGS RIMR 035c Page:18/20

RID 3082 ENVIRONMENTALLY 9 III HAZARDOUS SUBSTANCE,

LIQUID, N.O.S.

(EPOXIDE DERIVATIVES)

ICAO/IATA 3082 ENVIRONMENTALLY 9 III

HAZARDOUS SUBSTANCE,

LIQUID, N.O.S.

(EPOXIDE DERIVATIVES)

IMO/IMDG 3082 ENVIRONMENTALLY 9 III

HAZARDOUS SUBSTANCE,

LIQUID, N.O.S.

(EPOXIDE DERIVATIVES)

#### 14.5. Environmental hazards

Environmentally hazardous and/or Marine Pollutant : Yes.



**14.6** Special precautions for user : The state of the st

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7** Maritime transport in bulk according to IMO instruments

Not available

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU Regulation (EC) No. 1907/2006 (REACH)

### Annex XIV - List of substances subject to authorization

### **Annex XIV**

None required.

### **Substances of very high concern**

None required.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Restricted to professional users.

### Prior Informed Consent (PIC) (649/2012/EU)

None required.

### **Seveso Directive**

This product is controlled under the Seveso Directive.

### Danger criteria

Category	
E2	

### **International regulations**

#### International lists

: Australia inventory (AICS). All components are listed or exempted.

Canada inventory. All components are listed or exempted. Japan inventory All components are listed or exempted.

China inventory (IECSC). All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted.

New Zealand Inventory (NZIoC) All components are listed or exempted. Philippines inventory (PICCS). All components are listed or exempted. United States inventory (TSCA 8b). All components are active or exempted.

Taiwan inventory (TCSI). All components are listed or exempted.

Thailand inventory Not determined. Vietnam inventory Not determined.

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety

Assessments are still required.

No Chemical Safety Assessment has been carried out.

### **SECTION 16: Other information**

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360F	Calculation method
Aquatic Chronic 2, H411	Calculation method

### Full text of abbreviated H statements

H315 Causes skin irritation.	H315	
------------------------------	------	--

H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H360F	May damage fertility.	
H411	Toxic to aquatic life with long lasting effects.	

### Full text of classifications [CLP/GHS]

	AQUATIC HAZARD (LONG-TERM)
	SERIOUS EYE DAMAGE/ EYE IRRITATION
	SKIN CORROSION/IRRITATION
	SKIN SENSITIZATION
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A

Date of printing: 03.10.2024Date of issue/ Date of revision: 10.06.2024Date of previous issue: 01.06.2023Version: 6.0

### **Notice to reader**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.