

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Name : Spabond 440 Resin  
Product code : 21975  
Type of product : Epoxy resin  
Product group : Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd  
St Cross Business Park Newport  
GBR- PO30 5WU Isle of Wight  
United Kingdom  
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)  
[Regulatory@Gurit.com](mailto:Regulatory@Gurit.com) - [www.gurit.com](http://www.gurit.com)

#### 1.4. Emergency telephone number

Emergency number : Carechem 24Hrs: +44 (0) 1273 289451  
Telephone number for use in case of chemical exposure, spillage or fire only.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to GB CLP (SI 2019:720 as amended)

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360F
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

##### Adverse physicochemical, human health and environmental effects

May damage fertility or the unborn child. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP)



Signal word (GB CLP)

: Danger

Contains

: Formaldehyde, polymer with (chloromethyl)oxirane and phenol; reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700); oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether; Glycidoxypopyl Trimethoxysilane

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Hazard statements (GB CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H360F - May damage fertility. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (GB CLP)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P261 - Avoid breathing vapours. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment.

### 2.3. Other hazards

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5), reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3), oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2), 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8), Glycidoxypopyl Trimethoxysilane (2530-83-8)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5), reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3), oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2), 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8), Glycidoxypopyl Trimethoxysilane (2530-83-8)
Component	
Substance(s) not considered as endocrine disrupting. They are not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, nor identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)(1675-54-3), Formaldehyde, polymer with (chloromethyl)oxirane and phenol(9003-36-5), 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether(2425-79-8), oxirane, mono[(C12-14-alkyloxy)methyl] derivs.(68609-97-2), Glycidoxypopyl Trimethoxysilane(2530-83-8)

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	CAS-No.: 1675-54-3 EC-No.: 216-823-5	$\geq 50$	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	CAS-No.: 9003-36-5 EC-No.: 701-263-0	10 – 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
1,4-bis(2,3 epoxypoxy)butane; butanedioldiglycidyl ether	CAS-No.: 2425-79-8 EC-No.: 219-371-7	5 – 10	Acute Tox. 4 (Oral), H302 (ATE=1163 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F Aquatic Chronic 3, H412
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2 EC-No.: 271-846-8	3 – 5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360F
Glycidoxypropyl Trimethoxysilane	CAS-No.: 2530-83-8 EC-No.: 219-784-2	1 – 3	Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing vapours.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapours.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Maximum storage period : 2 year

Storage temperature : ≤ 30 °C Storage at elevated temperatures may cause pressure build-up in sealed containers

Storage area : Store away from heat. Store in a well-ventilated place.

Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

No additional information available

##### 8.1.2. Recommended monitoring procedures

No additional information available

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
Tyvek® Gown/Coveralls	EN 13034

##### Hand protection:

Protective gloves. Time of penetration is to be checked with the glove producer

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	0 (< 10 minutes)	0.26mm		EN ISO 374

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Respiratory protection			
Device	Filter type	Condition	Standard
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke when using this product.

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: Yellow.
Odour	: characteristic.
Odour threshold	: Not available
pH	: $\approx 6$
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flash point	: > 100 °C Estimated on the basis of the constituents :
Explosive limits	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 1,16 g/cm <sup>3</sup>
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: 10776 mm <sup>2</sup> /s
Viscosity, dynamic	: 12500 mPa·s
Explosive properties	: Not available

#### 9.2. Other information

VOC content	: 0 g/l VOC Directive (2004/42)
Particle characteristics	: Not applicable

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
-----------------------	------------------

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

LD50 oral rat > 10000 mg/kg

LD50 dermal rat > 2000 mg/kg

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

LD50 oral rat > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

LD50 dermal rat > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

### oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 oral rat 17100 mg/kg

LD50 oral 26,8 g/kg

LD50 dermal rabbit > 4000 mg/kg

### 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)

LD50 oral rat 1163 mg/kg

Skin corrosion/irritation : Causes skin irritation.  
pH: ≈ 6

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

pH 7

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

pH 6,12 – 6,64

### oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

pH 10

### 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)

pH 7

Serious eye damage/irritation : Causes serious eye damage.  
pH: ≈ 6

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

pH 7

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

pH 6,12 – 6,64

### oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

pH 10

### 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)

pH 7

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other., Remarks on results: other:
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other., Remarks on results: other:
IARC group	3 - Not classifiable

Reproductive toxicity : May damage fertility.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
NOAEL (animal/female, F0/P)	200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)
NOAEL (animal/female, F1)	200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Spabond 440 Resin	
Viscosity, kinematic	10776 mm²/s
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
Viscosity, kinematic	8,475 – 10,169 mm²/s

### Other information

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
LC50 - Fish [1]	< 1 mg/l
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
LC50 - Fish [1]	1,2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	2 mg/l
EC50 72h - Algae [1]	9,4 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'



# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

### 12.2. Persistence and degradability

#### Spabond 440 Resin

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) (1675-54-3)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

#### oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### Glycidoxypropyl Trimethoxysilane (2530-83-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 12.3. Bioaccumulative potential

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) (1675-54-3)

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### Component

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) (1675-54-3)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Glycidoxypropyl Trimethoxysilane (2530-83-8)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII

### 12.6. Other adverse effects

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700) (1675-54-3)**

Other information

Avoid release to the environment.




### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information	: Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
<b>14.1. UN number</b>		
UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.
<b>Transport document description</b>		
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) ; Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) ; Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) ; Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol), 9, III
<b>14.3. Transport hazard class(es)</b>		
9	9	9
		
<b>14.4. Packing group</b>		
III	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: True	Dangerous for the environment: True Marine pollutant: Yes	Dangerous for the environment: True
No supplementary information available		

#### 14.6. Special precautions for user

##### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR)	: -
EAC code	: •3Z

### Transport by sea

Special provisions (IMDG)	: 274, 335, 375, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

### Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

###### UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

###### UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC) above the 0.1% level of disclosure

###### GB PIC regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

###### POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

###### Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

###### Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

###### Drug Precursors Regulation (273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

##### 15.1.2. Other Information

VOC content : 0 g/l VOC Directive (2004/42)

#### 15.2. Chemical safety assessment

No additional information available

### SECTION 16: Other information

#### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

# Spabond 440 Resin

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

### Full text of H- and EUH-statements:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360F	Calculation method
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.