

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Name	: Spabond 400 Fast Hardener
UFI	: 4S8J-22CA-E004-83X1
Type of product	: Hardener (Crosslinker)
Synonyms	: Spabond 400 Fast Hardener
Product group	: Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category	: Industrial use, Professional use
-------------------	------------------------------------

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer	Other
Gurit (UK) Ltd	Gurit Spain SA
St Cross Business Park	Polígono Industrial Romica C/K
Newport	Parcela 11C, APDO.447
GBR PO30 5WU Isle of Wight	ESP 02080 Albacete
United Kingdom	Spain
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)	T +34 967 254 507, F +34 967 254 005
<a href="mailto:Regulatory@Gurit.com">Regulatory@Gurit.com</a> , <a href="http://www.gurit.com">www.gurit.com</a>	<a href="mailto:Regulatory@gurit.com">Regulatory@gurit.com</a> , <a href="http://www.Gurit.com">www.Gurit.com</a>

#### 1.4. Emergency telephone number

Emergency number	: Carechem 24Hrs: +44 (0) 1273 289451 Telephone number for use in case of chemical exposure, spillage or fire only.
------------------	--

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects. Harmful if swallowed.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	:	 
		GHS05      GHS07
Signal word (CLP)	:	Danger

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: 1,3-Propanediamine, N,N"-1,2-ethanediylbis-; Diethylene glycol bis(3-aminopropyl) ether; 1,3-Benzenedimethanamine; Phenol-formaldehyde polymer; Amines, polyethylenepoly-, triethylenetetramine fraction; 1,6-Hexanediamine, 2,2,4(or 2,4,4)-trimethyl-; Phenol, styrenated; 3-aminomethyl-3,5,5-trimethylcyclohexylamine
Hazard statements (CLP)	: H302 - Harmful if swallowed. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P260 - Do not breathe vapours. P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture contains substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component	
Substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Phenol, styrenated (61788-44-1)

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9 REACH-no: 01-2119514687-32	10 – 50	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
1,3-Benzenedimethanamine	CAS-No.: 1477-55-0 EC-No.: 216-032-5 REACH-no: 01-2119480150-50	10 – 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Phenol-formaldehyde polymer	CAS-No.: 9003-35-4 EC-No.: 500-005-2	5 – 25	Eye Irrit. 2, H319 Skin Sens. 1, H317
p-toluenesulphonic acid (containing a maximum of 5% H <sub>2</sub> SO <sub>4</sub> )	CAS-No.: 104-15-4 EC-No.: 203-180-0 EC Index-No.: 016-030-00-2 REACH-no: 01-2119538811-39	1 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,6-Hexanediamine, 2,2,4(or 2,4,4)-trimethyl-	CAS-No.: 25620-58-0; 25513-64-8 EC-No.: 247-063-2 REACH-no: 01-2119560598-25	1 – 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Amines, polyethylenepoly-, triethylenetetramine fraction	CAS-No.: 112-24-3; 90640-67-8 EC-No.: 292-588-2 REACH-no: 01-2119487919-13	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1,3-Propanediamine, N,N"-1,2-ethanediylbis-	CAS-No.: 10563-26-5 EC-No.: 234-147-9	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1A, H317
Diethylene glycol bis(3-aminopropyl) ether	CAS-No.: 4246-51-9 EC-No.: 224-207-2 REACH-no: 01-2119963377-26	1 – 5	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Phenol, styrenated substance identified as having endocrine disrupting properties	CAS-No.: 61788-44-1 EC-No.: 262-975-0	< 3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9 REACH-no: 01-2119514687-32	(0,001 ≤ C ≤ 100) Skin Sens. 1A; H317
p-toluenesulphonic acid (containing a maximum of 5% H2SO4)	CAS-No.: 104-15-4 EC-No.: 203-180-0 EC Index-No.: 016-030-00-2 REACH-no: 01-2119538811-39	(20 ≤ C ≤ 100) STOT SE 3; H335

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
-------------------------------------	---

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Protective equipment	: Protective clothing.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe vapours.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe vapours. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 30 °C Possible pressure build-up
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protection equipment

##### Personal protective equipment symbol(s):



#### Eye and face protection

##### Eye protection:

Safety glasses

#### Skin protection

##### Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
Tyvek® Gown/Coveralls	EN 13034

##### Hand protection:

Protective gloves. Time of penetration is to be checked with the glove producer

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	0 (< 10 minutes)	0.26mm		EN ISO 374

#### Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Respiratory protection			
Device	Filter type	Condition	Standard
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke during use. Industrial and professional. Perform risk assessment prior to use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Not available
Odour	: Amine-like.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not applicable
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not available
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≤ 1,085
Relative vapour density at 20°C	: Not applicable
Particle size	: Not available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Spabond 400 Fast Hardener

ATE CLP (oral)	1284,579 mg/kg bodyweight
----------------	---------------------------

#### p-toluenesulphonic acid (containing a maximum of 5% H<sub>2</sub>SO<sub>4</sub>) (104-15-4)

LD50 dermal rabbit	> 2000 mg/kg
--------------------	--------------

#### 1,3-Propanediamine, N,N"-1,2-ethanediylbis- (10563-26-5)

LD50 oral rat	≈ 1140 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 oral	950 mg/kg
LD50 dermal rabbit	> 200 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LD50 dermal	201 mg/kg

#### Diethylene glycol bis(3-aminopropyl) ether (4246-51-9)

LD50 oral rat	4290 mg/kg
LD50 dermal rabbit	2510 mg/kg

#### 1,3-Benzenedimethanamine (1477-55-0)

LD50 oral	980 (≤ 1180) mg/kg
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1,34 mg/l/4h

#### Phenol-formaldehyde polymer (9003-35-4)

LD50 oral rat	> 5 g/kg
---------------	----------

#### Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

LD50 oral rat	1716,2 mg/kg bodyweight
LD50 dermal rabbit	1465,4 mg/kg bodyweight

#### Phenol, styrenated (61788-44-1)

LD50 oral rat	2500 mg/kg
LD50 dermal rabbit	> 7940 mg/kg

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LD50 oral rat	1030 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,01 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.

#### Diethylene glycol bis(3-aminopropyl) ether (4246-51-9)

pH	> 12
----	------

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)</b>	
pH	13
Serious eye damage/irritation	: Causes serious eye damage.
<b>Diethylene glycol bis(3-aminopropyl) ether (4246-51-9)</b>	
pH	> 12
<b>Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)</b>	
pH	13
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>p-toluenesulphonic acid (containing a maximum of 5% H<sub>2</sub>SO<sub>4</sub>) (104-15-4)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
<b>1,3-Propanediamine, N,N"-1,2-ethanediylbis- (10563-26-5)</b>	
NOAEL (oral, rat, 90 days)	30 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified
<b>Diethylene glycol bis(3-aminopropyl) ether (4246-51-9)</b>	
Viscosity, kinematic	12,9 mm <sup>2</sup> /s
<b>11.2. Information on other hazards</b>	
<b>Endocrine disrupting properties</b>	
<b>Component</b>	
Phenol, styrenated (61788-44-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)
<b>SECTION 12: Ecological information</b>	
<b>12.1. Toxicity</b>	
Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
<b>1,3-Propanediamine, N,N"-1,2-ethanediylbis- (10563-26-5)</b>	
LC50 - Fish [1]	220 – 460 mg/l Test organisms (species): Leuciscus idus
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	7,2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>1,3-Benzenedimethanamine (1477-55-0)</b>	
EC50 72h - Algae [1]	12 mg/l

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

LC50 - Fish [1]	330 mg/l
EC50 - Crustacea [1]	31,1 mg/l
EC50 72h - Algae [1]	20 mg/l
NOEC chronic algae	< 2,5 mg/l

### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

EC50 - Crustacea [1]	14,6 – 21,5 mg/l (48 h - Species: Daphnia magna [semi-static])
EC50 72h - Algae [1]	37 mg/l (Species: Desmodesmus subspicatus)

## 12.2. Persistence and degradability

### Spabond 400 Fast Hardener

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### p-toluenesulphonic acid (containing a maximum of 5% H<sub>2</sub>SO<sub>4</sub>) (104-15-4)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 1,3-Propanediamine, N,N"-1,2-ethanediylbis- (10563-26-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### Diethylene glycol bis(3-aminopropyl) ether (4246-51-9)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 1,3-Benzenedimethanamine (1477-55-0)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### Phenol-formaldehyde polymer (9003-35-4)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 1,6-Hexanediamine, 2,2,4(or 2,4,4)-trimethyl- (25513-64-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### Phenol, styrenated (61788-44-1)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

## 12.3. Bioaccumulative potential

### Phenol, styrenated (61788-44-1)

Partition coefficient n-octanol/water (Log Pow)	> 4 (at 22 °C)
---	----------------

### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Partition coefficient n-octanol/water (Log Pow)	0,79 (at 23 °C)
---	-----------------

## 12.4. Mobility in soil

No additional information available

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

#### Component

Phenol, styrenated (61788-44-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)
---------------------------------	--

### 12.7. Other adverse effects

No additional information available




## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecological information	: Avoid release to the environment.
European List of Waste (LoW, EC 2000/532)	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
<b>14.1. UN number or ID number</b>		
UN 3259	UN 3259	UN 3259
<b>14.2. UN proper shipping name</b>		
POLYAMINES, SOLID, CORROSIVE, N.O.S.	POLYAMINES, SOLID, CORROSIVE, N.O.S.	Polyamines, solid, corrosive, n.o.s.
<b>Transport document description</b>		
UN 3259 POLYAMINES, SOLID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine ; 1,3-Propanediamine, N,N"-1,2-ethanediylbis-), 8, II, (E)	UN 3259 POLYAMINES, SOLID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine ; 1,3-Propanediamine, N,N"-1,2-ethanediylbis-), 8, II	UN 3259 Polyamines, solid, corrosive, n.o.s. (1,3-Benzenedimethanamine ; 1,3-Propanediamine, N,N"-1,2-ethanediylbis-), 8, II
<b>14.3. Transport hazard class(es)</b>		
8	8	8
		
<b>14.4. Packing group</b>		
II	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-A EmS-No. (Spillage): S-B	Dangerous for the environment: No

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: C8
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1kg
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P002, IBC08
Special packing provisions (ADR)	: B4
Mixed packing provisions (ADR)	: MP10
Portable tank and bulk container instructions (ADR)	: T3
Portable tank and bulk container special provisions (ADR)	: TP33
Tank code (ADR)	: SGAN, L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V11
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X

#### Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 kg
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P002
IBC packing instructions (IMDG)	: IBC08
IBC special provisions (IMDG)	: B21, B4
Tank instructions (IMDG)	: T3
Tank special provisions (IMDG)	: TP33
Stowage category (IMDG)	: A
Segregation (IMDG)	: SGG18, SG35
Properties and observations (IMDG)	: Colourless to yellowish solids with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Cause burns to skin, eyes and mucous membranes. React violently with acids.

#### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y844
PCA limited quantity max net quantity (IATA)	: 5kg
PCA packing instructions (IATA)	: 859
PCA max net quantity (IATA)	: 15kg
CAO packing instructions (IATA)	: 863
CAO max net quantity (IATA)	: 50kg
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

###### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

###### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

###### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

###### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

###### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

###### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

###### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

###### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

##### National regulations

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Not listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Not listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Germany

Air Quality Control (TA Luft)					
Category	Class	Applicable on	Local name	Max. mass flow	Max. mass concentration

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

A chemical safety assessment has been carried out

### SECTION 16: Other information

#### Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4

# Spabond 400 Fast Hardener

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Oral)	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.