

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bergolin LEP 6D1100, RAL7035

Product group: Produkt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

sciath polúireatán

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Bergolin GmbH & Co. KG
Street: Sachsenring 1
Place: D-27711 Osterholz-Scharmbeck
Telephone: +49 4795 95899 0
e-mail: info@bergolin.de
e-mail (Contact person): sdb@bergolin.de
Internet: www.bergolin.de
Responsible Department: Sicherheitsdatenblattverwaltung

1.4. Emergency telephone number:

+49 4795 95899 0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Sens. 1; H317
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra
reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)
-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)
-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)
-5-tert-butyl-4-hydroxyphenyl)propionylpoly(oxyethylene)
Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Poly(oxy-1,2-ethanediy),a-hydro-?-hydroxy- Ethane-1,2-diol, ethoxylated

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 2 of 10

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Polyurethan-Córas

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
136210-30-5	N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra			45 - < 50 %
	429-270-1		01-0000017556-64	
	Skin Sens. 1, Aquatic Chronic 3; H317 H412			
-	reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)			1 - < 5 %
	400-830-7	607-176-00-3		
	Skin Sens. 1, Aquatic Chronic 2; H317 H411			
41556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate			< 1 %
	255-437-1			
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			< 1 %
	280-060-4			
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
25322-68-3	Poly(oxy-1,2-ethanediy),a-hydro-?-hydroxy- Ethane-1,2-diol, ethoxylated			< 1 %
	500-038-2			
	Skin Sens. 1, Aquatic Chronic 2; H317 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
136210-30-5	429-270-1	N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra	45 - < 50 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 3 of 10

General information

When in doubt or if symptoms are observed, get medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.
After contact with skin, wash immediately with plenty of water and soap.
Do not wash with: Solvents/Thinner.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.
Seek medical advice immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let water be drunk in little sips (dilution effect).
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Hazardous decomposition products: carbon black. Health hazard.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
In case of fire: Wear self-contained breathing apparatus. Protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Avoid contact with skin, eyes and clothes.
Safe handling: see section 7
Personal protection equipment: see section 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 4 of 10

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed and suitable containers for disposal. Disposal: see section 13
Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear protective gloves/protective clothing. See section 8.
Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.
Persons with a history of skin sensitisation problems should not be employed in any process in which this product is used.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff. Only wear fitting, comfortable and clean protective clothing. Wash hands and face before breaks and after work and take a shower if necessary. Avoid contact with skin, eyes and clothes. Make available sufficient washing facilities

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

Hints on joint storage

Do not store together with: Oxidizing agent, Strong acid, Strong alkali,
Food and feedingstuffs

Further information on storage conditions

Notice the directions for use on the label.
Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 5 of 10

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7727-43-7	Barium sulphate, respirable dust	-	5		TWA (8 h)	
1317-65-3	Calcium carbonate, total inhalable dust	-	10		TWA (8 h)	
-	Dust non-specific, total inhalable	-	10		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
136210-30-5	N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra			
Worker DNEL, acute	inhalation	systemic		112 mg/m ³
Worker DNEL, long-term	inhalation	systemic		28 mg/m ³
Worker DNEL, long-term	dermal	systemic		4 mg/kg bw/day
Consumer DNEL, acute	inhalation	systemic		4,8 mg/m ³
Consumer DNEL, acute	dermal	systemic		1,4 mg/kg bw/day
Consumer DNEL, acute	oral	systemic		1,4 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic		4,8 mg/m ³
Consumer DNEL, long-term	dermal	systemic		1,4 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic		1,4 mg/kg bw/day
7727-43-7	barium sulfate			
Worker DNEL, long-term	inhalation	systemic		10 mg/m ³
Worker DNEL, long-term	inhalation	local		10 mg/m ³
Consumer DNEL, long-term	inhalation	systemic		10 mg/m ³
Consumer DNEL, long-term	oral	systemic		13000 mg/kg bw/day

PNEC values

CAS No	Substance	Value
136210-30-5	N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra	
Freshwater		0,00013 mg/l
Marine water		0,000013 mg/l
Freshwater sediment		0,21 mg/kg
Marine sediment		0,02 mg/kg
Soil		0,1 mg/kg
7727-43-7	barium sulfate	
Freshwater		0,115 mg/l
Freshwater sediment		600,4 mg/kg
Soil		207,7 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 6 of 10

worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.
goggles Eye glasses with side protection

Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: rubair búitleach nó Viton (is gá go mbeadh resistance ar an ábhar agus See information supplied by the manufacturer.

Breakthrough time (maximum wearing time): ____ min.

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing Suitable material: Natural fibres (e.g. cotton) / heat-resistant synthetic fibres.

Respiratory protection

Usually no personal respirative protection necessary.
Respiratory protection necessary at: exceeding exposure limit values.
Suitable respiratory protection apparatus: Scagtha teaghlaim A-P2
Chun obair i bpótaí agus umair: Scagtha teaghlaim A-P4

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	grey
Odour:	characteristic

Test method

Changes in the physical state

Melting point/freezing point:	not determined
-------------------------------	----------------

Boiling point or initial boiling point and boiling range:	300 °C
---	--------

Flash point:	> 115 °C DIN 53213
--------------	--------------------

Flammability

Solid/liquid:	not determined
---------------	----------------

Gas:	not determined
------	----------------

Explosive properties

No information available.

Auto-ignition temperature:	375 °C
----------------------------	--------

Flow time: (at 20 °C)	> 100
--------------------------	-------

Water solubility:	not determined
-------------------	----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 7 of 10

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:
(at 20 °C)

<0,00002 hPa

Density (at 20 °C):

1,46 g/cm³ DIN 53217

9.2. Other information

Sustaining combustion:

No data available

Oxidizing properties

No information available.

Solvent separation test:

<3 % (Land transport (ADR/RID))

Solvent content:

0,07 %

Solid content:

99,93 %

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

10.4. Conditions to avoid

May form hazardous decomposition products when exposed to high temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
136210-30-5	N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 8 of 10

Sensitising effects

May cause an allergic skin reaction. (N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra; reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene); Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; Poly(oxy-1,2-ethanediyl),a-hydro-?-hydroxy-Ethane-1,2-diol, ethoxylated)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Following inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Depression of central nervous system.

Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

Following skin contact:

May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
136210-30-5	N, N-(4,4-dicyclohexylmethane-diyl-bis-asparaginsäuretetra					
	Acute fish toxicity	LC50	66 mg/l	96 h	Danio rerio	
	Acute crustacea toxicity	EC50	88,6 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
not applicable

12.6. Endocrine disrupting properties

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 9 of 10

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.
Recycle according to official regulations.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.
Recycle according to official regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): 0,072 % (1,048 g/l)

2004/42/EC (VOC): 0,072 % (1,048 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergolin LEP 6D1100, RAL7035

Revision date: 29.07.2021

Product code: A1019253

Page 10 of 10

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,9,15.

Abbreviations and acronyms

ADR - Accord européen relatif transport des marchandises dangereuses par route ATE - Acute Toxicity Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS - Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - „Derived No-Effect Level“; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)